

Series Scrubber Specifications



AUTHORIZED DISTRIBUTOR

BODY CONSTRUCTION / DIMENSION	IS
Tank Material:	Poly 3/8" (9.5 mm)
Chassis Construction:	3/16" (4.7 mm) Powder Coated Steel
Front Wheels (Diameter × Width):	(2x) 10" x 2.5" ([2x] 25.4 x 6.4 cm) - Non-Marking Solid Grey
Rear Casters (Diameter × Width):	(2x) 4" x 2" ([2x] 10.2 × 5.1 cm) - Non-Marking Grey
Size (L \times W \times H):	52" × 22" × 40" (<i>132.1</i> × 55.9 × 101.6 cm)
Weight (w/o Batteries):	393 - 443 lbs (178.3 - 200.9 kg)
Weight (w/ 210 ah Batteries):	625 - 675 lbs (283.5 - 306.2 kg)
BRUSH / PAD SYSTEM	
Disk Dimensions: Includes Jaws with Rollers for Wall Protection	26" - (2×) 13" Diameter (66 - [2×] 33 cm) 28" - (2×) 14" Diameter (71.1 - [2×] 35.6 cm)
Disk Motor:	(2×) 0.75 hp / 350 rpm ([2×] 559 watts)
Disk Brush Speed:	350 rpm
Cylindrical Dimensions: 6" Diameter Brush	25" - (2×) 6" × 23" (63.5 - [2×] 15.2 × 58.4 cm) 29" - (2×) 6" × 27" (73.7 - [2×] 15.2 × 68.6 cm)
Cylindrical Motor:	25" - (2×) 0.75 hp / 350 rpm ([2×] 559 watts) 29" - (2×) 1.0 hp / 350 rpm ([2×] 746 watts)
Cylindrical Brush Speed:	750 rpm
EDGE Dimensions:	24" × 14" (70 × 35.6 cm) 28" × 14" (71.1 × 35.6 cm)
EDGE Motor:	1.0 hp / 2500 rpm (746 watts)
EDGE Optional HD Motor:	1.2 hp / 2900 rpm (894 watts)
Actuator Rating:	500 lbs (226.8 kg)
Brush Pressure Settings:	(5) with Auto Adjust
POWER SYSTEM	
System Voltage:	24 VDC
Standard Battery:	210 ah WET
Optional Battery: *Includes Onboard Charger	245 ah WET / 250 ah AGM*
Run Time: **Run times are based on continuous scrubbing run times.	Up to 3.5 Hours**
Charger:	24 VDC / 25 amp / 120 V / 60 Hz
DRIVE SYSTEM:	
Power:	0.75hp - All Gear / Sealed (559 watts)
Forward Speed:	0 - 290 ft/min <i>(3.3 mph)</i> 0 - 88 m/min <i>(5.3 km/h)</i>
Reverse Speed:	0 - 202 ft/min (2.3 mph) 0 - 62 m/min (3.7 km/h)
SOLUTION / RECOVERY SYSTEMS:	
Solution Tank Capacity:	21 Gallons (79.5 liters) - w/ Graduated Site Tube Indicator
Solution Flow / Filter:	0 - 0.7 GPM / Stainless Inline (0 - 2 LPM)
Recovery Tank Capacity:	23 Gallons (87.1 liters) - 1.5" diameter Drain Hose
Demisting Chamber:	1.25 Gallons (4.7 liters)
Drain Saver:	30 cubic inches (491.6 cubic cm)
Vacuum Power:	0.8 hp / 3 Stage (640 watts)
Vacuum Specs (Water Lift / Airflow):	68" / 72 cfm (172.7 cm / 2 cm/m)
Squeegee:	36" Curved w/ 4-sided Rear Blade & Quick Change Latch
GENERAL:	
Cleaning Width:	26" & 28" - Disk (66 & 71.1 cm) 25" & 29" - Cylindrical (63.5 & 73.7 cm) 24" & 28" - EDGE (70 & 71.1 cm)
Decibels:	67 dB
Productivity - Theoretical: ***Productivity is based off of ISSA 2010 Cleaning Times	Up to 27,027 sqft (2,510.9 sqm)***
Productivity - Practical: ***Productivity is based off of ISSA 2010 Cleaning Times	Up to 12,526 sqft (1,163.7 sqm)***